

# ECODIN RS

## Chemical release agent based on sustainable oils - BCA (C&A) Category 7

### DESCRIPTION

**ECODIN RS** is a readily biodegradable chemical release agent specially formulated to give easy release from pre-cast moulds or formwork and provides a high quality surface finish to concrete. The product utilizes sustainable Vegetable Oils within its formulation.

### ADVANTAGES

- **ECODIN RS** is environmentally sustainable product based on green vegetable oils
- **ECODIN RS** is suitable for use on all types of formwork and pre-cast mould materials.
- It is a suspension and sediment free, highly mobile liquid, which can be used in very fine sprays without clogging the jets.
- There is no unpleasant odour, even when using a fine fog spray.
- Very economic coverage rates can be obtained without difficulty.
- Retains its mobility at low temperatures.
- It may be applied immediately prior to casting, or treated forms may be left until apparently dry.
- Continued use gives progressively better results on timber formwork.
- Can be used with either grey or white cement.
- Provides a quick, positive release of formwork, reducing labour costs and damage to formwork and moulds.

### PROPERTIES

Appearance:	Clear yellow, low viscosity
Specific Gravity:	0.88 @ 20°C
Flash Point:	75°C (PMCC)
Viscosity:	5.0 cST @ 40°C
Freezing Point:	<-5°C
Storage Life:	Sealed containers stored above 5°C and below 30°C will have a minimum of 12 months shelf life.

### COVERAGE

25 to 60m<sup>2</sup>/litre dependent on type of form, porosity, texture of surface and ambient temperature.

## Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR  
Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)

## APPLICATION

**ECODIN RS** is ready for use and should not be diluted. The product should be applied as thinly and evenly as possible. It can be applied to all types of formwork by spray, or absorbent applicator. Any excess should be mopped up. For the best and most economical performance, application by mist spray is recommended. Excellent results can be obtained using a Gloria 410T or Mesto Ferrox Plus sprayer with a 8001 tip fitted.

Many new forms are not factory treated with oils, so for new or 'unsealed' timber formwork, pre-treatment is essential with two coats prior to use. This will extend the useful life of the form and help to standardise surface absorbency. Consideration should also be given to sealing using **SHUTTAWAX** or **FORMSEAL PU 1K** which will extend the useful life of ply.

## STORAGE & HANDLING

Containers must be kept sealed after use. This type of material should be applied in well ventilated areas. Keep away from naked flames and electrical equipment. Please refer to Material Safety Data Sheet for further details. Manufacturer sealed containers stored above 5°C and below 30°C will have a minimum of 12 months shelf life. Once opened use within 6 months.

## HEALTH & SAFETY

Refer to separate safety data sheet. Copies available by request

## PACKAGING & TRANSPORT

Supplied in 1000ltr IBC, 200ltr, 25ltr. Not Regulated for Road Transport

## QUALITY ASSURANCE

Norsekem Limited Products are manufactured under quality assured schemes

Norsekem Limited products are guaranteed against defective materials and manufacture. Products are sold subject to the Norsekem Limited Terms and Conditions of Sale, copies of which are available on request. Norsekem Limited endeavors to ensure that the above data and any further advice is correct, Norsekem Limited can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not over-ride the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.

## Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR

Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)