

# FORMKLEEN

Biodegradable, cement remover and degreaser for all types of metal surfaces

## DESCRIPTION

**FormKleen** was originally developed in Scandinavia as a biodegradable, low hazard, hard surface cleaner for removing cement films and deposits from the pallet rings in Precast Spun Pipe factories.

The dual action product is a unique blend of surface active ingredients, sequestrates and organic scale removers specifically designed to cut through and remove the mould oil and allow the organic descalers to work on the cement deposits.

## USES

**FormKleen** can be used to clean down metal formwork in Pre-cast factories and on site erected formwork panels. Safe with aluminium but will dull if shiny.

All sorts of construction plant can be cleaned to remove scale and cement films. Ideal for concrete lorries, mobile and static concrete pumps, concrete pan mixers, cement mixers, etc. Safe on paintwork.

Can also be used to effectively clean washrooms, toilets and showers.

## ADVANTAGES

- Effective at high dilution in both hard & soft waters
- Biodegradable
- Easily and gently removes oil dirt, grime, limescale and cement films
- Does not contain, ingredients which accelerate metal corrosion
- Safe on tiles, paintwork, metal surfaces, glass and rubber
- Works in both cold and hot pressure wash machines

## PROPERTIES

Appearance:	Clear Red Fluid
Specific Gravity @ 20°C:	1.060
Odour:	Bland
pH of neat % Solution:	2.0 Typical
pH of 5% Solution:	2.0 Typical

### Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR

Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)

## APPLICATION

### *For Construction Vehicle/Plant Cleaning:-*

Dilute with water between 1:20 and 1:100 depending on degree of soiling and as recommended by your pressure wash machine manufacturer. Can be applied by separate plastic sprayer.

Apply via low pressure as foam to Vehicle/Plant.

### *For Heavy Duty De-Scale & Cleaning*

Dilute 1:50 with water and apply liberally all over surface or equipment, Allow a few minutes contact time, agitate with brush if required, then rinse well. This product may be used neat on severely encrusted parts but care must be taken.

### *General Mould or Hard Surface Cleaning*

For general removal of dirt and cement scale use in diluted form, 1:20 and 1:100 with water. Application is most economic with use of an all plastic sprayer. Allow a few minutes contact time, agitate with brush, sponge etc if required, rinse with high pressure jet or hose and repeat as necessary.

## COVERAGE

Dependent on dilution

## STORAGE & HANDLING

Do not store in metal containers or sprayers. No special storage conditions are needed although being water based avoid long term storage in sub zero temperatures

## HEALTH & SAFETY

Refer to separate material safety data sheet. Copies available by request

## PACKAGING & TRANSPORT

Supplied in 1000ltr IBC, 205ltr, 25ltr and 5ltr plastic drums. Not Regulated for Road Transport

## QUALITY ASSURANCE

Norsekem Limited Products are manufactured under quality assured schemes

Norsekem Limited products are guaranteed against defective materials and manufacture. Products are sold subject to the Norsekem Limited Terms and Conditions of Sale, copies of which are available on request. Norsekem Limited endeavors to ensure that the above data and any further advice is correct, Norsekem Limited can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not over-ride the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.

## Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR

Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)