

POLY-DISSOLVE 'SAFE'

Safe, low hazard polystyrene dissolver and solvent emulsifier

DESCRIPTION

Developed to dissolve and emulsify expanded polystyrene commonly used in the Concrete Construction and Pre-Cast Industries, these include void formers, stop ends, box outs and inserts. It is formulated to be safe for the user and carries a no-hazard label making it more user friendly. Has a pleasant citrus odour.

APPLICATION

POLY-DISSOLVE SAFE should be used neat as supplied. The preferred method of application is by pouring from a non-pressured apparatus such as a watering can with a fine rose fitted. Only a small quantity is required to dissolve quite large sections of polystyrene. Once a liquid residue has been formed, wash away with water or wipe away with a damp cloth. If the residue is left for a while it will solidify, this can easily be liquefied again by further application of **POLY-DISSOLVE SAFE**.

PROPERTIES

| | |
|-------------------|---------------------------------|
| Appearance: | Pale Amber, low viscosity Fluid |
| Specific Gravity: | 1.040 @ 20°C |
| Flash Point: | 88°C (PMCC) |
| Viscosity: | 2.2 cSt @ 20°C |
| Boiling Point: | 173-250°C |
| Storage Life: | Indefinite in sealed drums. |

COVERAGE

Dissolve up to 10 times its own volume, actual results will vary depending on polystyrene density and application. We can not give actual application rates as there are too many variables. Site trials will determine the optimum usage.

STORAGE & HANDLING

Manufactured in sealed drums. Requires no special storage facilities. Material should be applied in well ventilated areas. Keep away from naked flames, electrical equipment, foodstuffs and children.

HEALTH & SAFETY

Refer to separate safety data sheet. Copies available on request. If spraying, care should be taken to minimise inhalation and contact with eyes and ensure adequate ventilation during application.

PACKAGING & TRANSPORT

Supplied in 5ltr plastic bottles, 25ltr, 200ltr steel drums and 1000ltr IBC tanks.

QUALITY ASSURANCE

Norsekem Limited Products are manufactured under quality assured schemes
Norsekem Limited products are guaranteed against defective materials and manufacture. Products are sold subject to the Norsekem Limited Terms and Conditions of Sale, copies of which are available on request. Norsekem Limited endeavors to ensure that the above data and any further advice is correct, Norsekem Limited can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not over-ride the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.

Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR

Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

norsekem.co.uk