

# TEKNIGUARD

## Protection for concrete mixing and placing equipment

### DESCRIPTION

**TekniGuard** is a special blend of oils and active ingredients that will form a protective layer to help stop concrete adhering to all sorts of Concrete Mixing and Placing Equipment, including Pan Mixers, Concrete Pumps, Concrete Lorries. This makes removal of the concrete that much easier by high pressure water techniques. The product does not contain any solvents so is safer on rubber seals etc.

### ADVANTAGES

- Provides a protective coating that stops concrete adhering to metal surfaces.
- Economic coverage rates can be obtained using spray equipment.
- Does not contain solvents.
- Helps prevent corrosion caused by cement on metal.
- Lubricates and cleans without the risk of using acid based products.
- Greatly reduces cleaning and maintenance costs.

### PROPERTIES

Appearance:	Clear light straw, low viscosity
Specific Gravity:	0.85 @ 20°C
Flash Point:	150°C
Viscosity:	>12c/st @ 40°C
Freezing Point:	<0°C
Storage Life:	Indefinite in sealed drums.

### COVERAGE

Up to 60m<sup>2</sup>/litre

## Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR  
Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)

## APPLICATION

**TekniGuard** is ready for use and should not be diluted. It should be applied as thinly and evenly as possible for optimum performance.

For the best and most economical performance, application by mist spray is recommended. Excellent results can be obtained using a Gloria 410T Sprayer or a Mesto Ferrox Plus sprayer with an 8002 tip fitted.

It is advisable to apply regularly, ideally as part of a daily preventative maintenance and cleaning schedule.

## STORAGE & HANDLING

**TekniGuard** in manufacturer's sealed drums requires no special storage facilities. Material should be applied in well ventilated areas.

Keep away from naked flames, electrical equipment, foodstuffs and children.

## HEALTH & SAFETY

Refer to separate material safety data sheet. Copies available by request.

If spraying, care should be taken to minimise inhalation and contact with eyes and ensure adequate ventilation during application.

## PACKAGING & TRANSPORT

Supplied in 25ltr, 200ltr, 1000ltr IBC tanks. Not Regulated for Road Transport

## QUALITY ASSURANCE

Norsekem Limited Products are manufactured under quality assured schemes.

Norsekem Limited products are guaranteed against defective materials and manufacture. Products are sold subject to the Norsekem Limited Terms and Conditions of Sale, copies of which are available on request. Norsekem Limited endeavors to ensure that the above data and any further advice is correct, Norsekem Limited can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not over-ride the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.

## Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR

Tel: 08454027663 Fax: 0845 4027662 Email: [sales@norsekem.co.uk](mailto:sales@norsekem.co.uk)

[norsekem.co.uk](http://norsekem.co.uk)